Hybrid Digital Twins: A Proof of Concept for Reinforced Concrete Beams

Tarik Sahin¹, M. von Danwitz¹, T. T. Kochmann¹, Alexander Popp¹

¹Institute for Mathematics and Computer-Based Simulation, University of the Bundeswehr Munich, Germany

der Bundeswehr Universität 🙀 München

Motivation

Digital twins map real objects and processes from the physical world into digital space. Going one step further, hybrid digital twins (HDT) combine physics-based modeling (virtual twin) with data-based techniques (digital twin) to form a simulation tool with predictive power.



In light of the increasing digitalization of our world, digital twins have great potential to contribute to protecting and maintaining critical infrastructures. In case of bridges, digital twins can have a crucial role in structural health monitoring (SHM) [1].

Physics-Based Full-Order Model





The physics-based FOM is based on a novel finite element formulation with beam-tosolid mesh tying. We use this method to capture the interaction between the reinforcement components and the concrete matrix of the beam [2].

Data-Driven Reduced-Order Model

Physics-informed neural networks





Proof of Concept

This contribution provides proof of the concept of a hybrid digital twin for steel-reinforced concrete beams as a representative component of bridges in civil engineering structures.



We combine a physics-based full-order model (FOM) with a fast-toevaluate data-driven reduced-order model (ROM) interacting with sensor data of the physical asset. The full-order model provides a detailed understanding of the physical behavior and is employed to calibrate the reduced-order model aiming at a reliable digital representation. The combined model has the following capabilities:

- damage, crack and anomaly detection
- "what-if" simulations

The data-driven ROM is based on **p**hysics-**i**nformed **n**eural **n**etworks (PINNs) that combine differential equations and measurement data in the loss function of neural networks [3].

Use Cases



identification of underlying trends

Acknowledgement

This research is funded by dtec.bw -Digitalization and Technology Research Center of the Bundeswehr [project RISK.twin].



- Comparison of estimated strains of FOM and ROM with measurements
- Detection of crack centers and damaged regions using purely data-driven ROM
 Anomaly detection in SHM

References

Thomas Braml, Johannes Wimmer, and Yauhen Varabei. Erfordernisse an die Datenaufnahme und -verarbeitung zur Erzeugung von intelligenten Digitalen Zwillingen im Ingenieurbau (Requirements to data acquisition and processing for the generation of intelligent digital twins in civil engineering). In *Innsbrucker Bautage 2022 (eds Berger, J.) (Studia, 2022)*, pages 31–49, 2022.
 Ivo Steinbrecher, Matthias Mayr, Maximilian J Grill, Johannes Kremheller, Christoph Meier, and Alexander Popp. A mortar-type finite element approach for embedding 1d beams into 3d solid volumes. *Computational Mechanics*, 66(6):1377–1398, 2020.

[3] Lu Lu, Xuhui Meng, Zhiping Mao, and George Em Karniadakis. Deepxde: A deep learning library for solving differential equations. SIAM Review, 63(1):208–228, 2021.

www.unibw.de/imcs

tarik.sahin@unibw.de